Автор: Administrator
13.06.2014 17:09

{jcomments on}

Решение:

```
 #include <stdio.h>  #include <stdlib.h>  #include <math.h>  #include <conio.h>  #include
<iostream.h>    unsigned int factor(int x)   {  unsigned int f = 1;  for (int i = 2; i <= x; i++)  f *= i;
return(f) ; }  void main()  {  unsigned int f;  printf ("nThe Program of the calculation of the amount
factorial uneven from 1 before 9n");  printf ("nTable factorial uneven from 1 before 9n");  for (int
n = 1; n <= 1; n++)  {  f = factor(n); printf("%i %un", n,f);   }  for (int n1 = 3; n1<= 3; n1++)  {  f =
factor(n1); printf("%i %un", n1,f);   }  for (int n2 = 5; n2<= 5; n2++)  {  f = factor(n2); printf("%i
%un", n2,f);   }  for (int n3 = 7; n3<= 7; n3++)  {  f = factor(n3); printf("%i %un", n3,f);   }  for (int
n4 = 9; n4<= 9; n4++)  {  f = factor(n4); printf("%i %un", n4,f);  }  int c;   printf ("nAmount factorial
from 1 before 9n");  if (n--,n1--,n2--,n3--,n4--,c,f)  {
c=factor(n)+factor(n1)+factor(n2)+factor(n3)+factor(n4);  printf ("n
%d+%d+%d+%d+%d",factor(n),factor(n1),factor(n2),factor(n3),factor(n4));  printf ("=%d",c);  }
getch();  }
```

(function(w, d, n) { w[n] = w[n] || []; w[n].push({ section_id: 263974, place: "advertur_263974",
width: 300, height: 250 }); })(window, document, "advertur_sections");